



tesa® 51618

Product Information



PET fleece wire harness tape for the passenger compartment

Product Description

tesa® 51618 is the universal tape for wire harness bundling in the passenger compartment. It combines features as noise damping, abrasion resistance and bundling strength while keeping harnesses flexible enabling an easy harness assembly process at the OEM. tesa® 51618 is for manual application.

- noise damping
- abrasion resistant
- flexible and smooth
- tear resistant
- stable unwind force
- resistant to ageing
- strong adhesion
- hand tearable

Application Fields

tesa® 51618 is a wire harness tape designed for the passenger compartment, providing flexibility and noise damping.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Properties/Performance Values

• Elongation at break	20 %	• Noise damping (LV312)	Class C
• Tensile strength	37 N/cm	• Temperature resistance max	105 °C
• Abrasion resistance (10mm mandrel, LV312)	Class B	• Unwind force (roll width > 9mm)	9 N/roll (30 m/min)
• Abrasion resistance (5mm mandrel, LV312)	Class A	• Unwind force (roll width ≤ 9mm)	9 N/roll (30 m/min)
• Minimum temperature resistance	-40 °C		

Adhesion to Values

- steel 3 N/cm

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 15, 25 m

- Most combinations of width and length are possible
- Further dimensions are available upon request

For latest information on this product please visit <http://l.tesa.com/?ip=51618>



tesa® 51618

Product Information

Additional Information

- Standard core diameter: 38 mm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=51618>