

tesa® EasySplice 51910 FilmLine PLUS

Product Information



Product Description

tesa® 51910 EasySplice® FilmLine PLUS is an integrated flying splice tape consisting of a paper backing and a modified synthetic rubber adhesive.

tesa® 51910 EasySplice® FilmLine PLUS features especially

- Very high tack properties
- Very good adhesion values on PE and PP films
- Low splice thickness
- Printable backing

The innovative tape composition includes the following functions:

- Slit liner for the secure fixation of the top sheet
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- One splitting strip with tailored opening characteristics for a smooth opening of the new reel without jeopardizing the printing process

Application Fields

tesa® 51910 EasySplice® FilmLine PLUS is particularly suitable for:

- Flying splices in the flexography or rotogravure printing industry of flexible packaging material, as well as for critical substrates like breathing film.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Backing material | Paper | • Total thickness | 120 µm |
| • Type of adhesive | synthetic rubber | • Colour | pink |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 6 % | • Shelf life time (packed) < 25°C | 21 months |
| • Tensile strength | 30 N/cm | | |

tesa® EasySplice 51910 FilmLine PLUS

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51910>