



# tesa® 4169

## Product Information



### Premium Floor Marking Tape

#### Product Description

tesa® 4169 PV3 is a lane marking tape with a PVC backing and water-based acrylic adhesive. It is perfect suited to permanent marking applications.

#### Application Fields

- Marking of working areas e.g. in factories and warehouses.
- Guiding lines for mark special vehicles e.g. transport robots.
- Marking of parking spaces and gangways in offices, hospitals, fairs etc..

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Product Construction

- |                    |          |                   |        |
|--------------------|----------|-------------------|--------|
| • Backing material | soft PVC | • Total thickness | 187 µm |
| • Type of adhesive | acrylic  |                   |        |

#### Properties/Performance Values

- |                    |           |
|--------------------|-----------|
| • Tensile strength | 42.5 N/cm |
|--------------------|-----------|

#### Additional Information

The plain colours of tesa® 4169 PV3 are according to the RAL colour scheme.

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04169>