



# tesa® 60760 PV1



## Product Information

### Floor Marking Tape

### Product Description

tesa® 60760 is a tough plasticised PVC tape coated with an aggressive modified rubber-resin adhesive which allows adhesion on many different surfaces. tesa® 60760 is also hand tearable.

### Product Features

- Color combinations correspond to legally prescribed safety guidelines
- tesa®60760 has a flexible backing to cope with curves
- Durable and robust backing for floor marking applications; hand tearable
- Depending on its color, the floor-marking tape can be explicitly used as a warning tape.
- The modified natural rubber adhesive provides good adhesion to various surfaces.
- Thanks to the high degree of flexibility of the backing, it can also be used on rough surfaces and is also suitable for curved applications.

### Application Fields

tesa® 60760 is perfectly suitable for temporary and low duty hazard warning & marking of any kind of mobile or static objects.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing material | soft PVC       | • Total thickness | 150 µm |
| • Type of adhesive | natural rubber |                   |        |

### Properties/Performance Values

- |                       |         |                      |    |
|-----------------------|---------|----------------------|----|
| • Elongation at break | 220 %   | • Batteries included | no |
| • Tensile strength    | 33 N/cm | • Batteries required | no |

### Adhesion to Values

- |         |        |
|---------|--------|
| • steel | 2 N/cm |
|---------|--------|



# tesa<sup>®</sup> 60760 PV1

## Product Information

## Additional Information

tesa<sup>®</sup> 60760 is also available in two highly visible colour combinations in accordance with safety regulations.

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60760>