



tesa® 51616

Product Information



Thick PET- fleece wire harness tape for high noise reduction

Product Description

tesa® 51616 is the cost efficient solution providing excellent noise reduction and a high abrasion resistance. It is for manual application on wire harnesses.

Features:

- hand tearable
- very high sound damping
- temperature resistance 125°C/3000h
- resistant to ageing
- rot-proof
- strong adhesion
- flexible and smooth

Application Fields

tesa® 51616 is a wire harnessing tape designed for the passenger compartment, providing high noise damping.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Properties/Performance Values

• Elongation at break	50 %	• Noise damping (LV312)	Class D
• Tensile strength	30 N/cm	• Temperature resistance max	105 °C
• Abrasion resistance (10mm mandrel, LV312)	Class D	• Unwind force (roll width > 9mm)	12 N/roll (30 m/min)
• Abrasion resistance (5mm mandrel, LV312)	Class C	• Unwind force (roll width ≤ 9mm)	12 N/roll (30 m/min)
• Minimum temperature resistance	-40 °C		

Adhesion to Values

- | | |
|---------|--------|
| • steel | 3 N/cm |
|---------|--------|

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 7.5 m

- Most combinations of width and length are possible
- Further dimensions are available upon request

For latest information on this product please visit <http://l.tesa.com/?ip=51616>



tesa® 51616

Product Information

Additional Information

- Standard core diameter: 38 mm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=51616>