



tesa[®] PRO 74662 STRONG Duct tape



Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PE-film with PET-filament	• Total thickness	215 µm
• Type of adhesive	synthetic rubber		

Properties/Performance Values

• Elongation at break	19 %	• Mesh	27 count per square inch
• Tensile strength	40 N/cm	• Straight tear edges	good, medium
• Abrasion resistance	good	• Tack	very good
• Easy to remove	no	• Unwind force n/cm	2 N/cm
• Easy to write on	no	• Water resistance	good, medium
• Hand tearability	very good		

Adhesion to Values

• rough surfaces	6.5 N/cm	• steel	8 N/cm
------------------	----------	---------	--------

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=74662>