

tesa® 5225

Crack Cover

Product Information

Flexibe fleece tape for surface preparation prior to painting and wallpapering

Product Description

When it comes to painting or wallpapering your home, a perfectly smooth surface is the key to professional-quality results. tesa® Crack Cover is a highly thin yet flexible fleece tape especially designed for wall and ceiling crack repair. It is also ideal for drywall crack repair and serves to fix all kinds of imperfections of the surface of a wall. Use this extra thin self-adhesive tape to cover cracks, seams and holes during surface preparation*. This will keep wallpapers from tearing and prevent a coat of paint from showing unsightly cracks shortly after it was applied.

*There is a possibility that the painted Crack Cover tape may be visible

Product Features

- Covers cracks and seams
- * Self-adhesive
- * Minimal elevation
- * Paint and wallpaper can be applied immediately after use
- * Prevents wallpaper tearing permanently
- * *There is a possibility that the painted Crack Cover tape may be visible

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------|-------------------|--------|
| • Backing material | non-woven | • Total thickness | 110 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------|---------|------------------------|-----|
| • Tensile strength | 16 N/cm | • Residue free removal | no |
| • Hand tearability | good | • UV-resistant | yes |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 1.1 N/cm |
|---------|----------|

tesa® 5225 Crack Cover

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=5225>