



tesa® Adjustable Adhesive Screw for Tiles & Metal 3kg



Product Information

BNR 77765

Product Description

Height adjustable adhesive screw for up to 3kg. Perfect for mounting decorative objects and kitchen utensils on smooth and solid surfaces like tiles and metal. Height adjustable adhesive screw for up to 3kg. Perfect for mounting decorative objects and kitchen utensils on smooth and solid surfaces like tiles and metal.

Product Features

- For smooth and solid surfaces like tiles indoors
- For objects up to 3kg per screw or 6kg using 2 screws
- Height adjustable for straight alignment of objects
- Removable without a trace
- Reusable with a new strip
- For smooth and solid surfaces like tiles indoors
- For objects up to 3kg per screw or 6kg using 2 screws
- Height adjustable for straight alignment of objects
- Removable without a trace
- Reusable with a new strip

Application Fields

||

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|--------------------------------|------|
| • Type of adhesive | synthetic rubber | • Holding power of strip up to | 3 Kg |
|--------------------|------------------|--------------------------------|------|

Properties/Performance Values

- | | | | |
|--------------------------------|------------------|------------------------|-----|
| • Application temperature from | -15 °C | • Ozone resistance | no |
| • Chemical resistance | no | • Residue free removal | yes |
| • Hazard material | no | • Reusable | yes |
| • Humidity resistance | no | • UV-resistant | no |
| • Material | PS (polystyrene) | • Waterproof | no |
| • Oil and grease resistance | no | | |



tesa[®] Adjustable Adhesive Screw for Tiles & Metal 3kg

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>