



# tesa<sup>®</sup> Adhesive Nail for Wallpaper & Plaster 2kg



## Product Information

BNR 77776

## Product Description

Adhesive Nail for up to 2kg. Ideal for hanging decorative items like pictures on textured and sensitive surfaces like wallpaper or plaster. Adhesive Nail for up to 2kg. Ideal for hanging decorative items like pictures on textured and sensitive surfaces like wallpaper or plaster.

## Product Features

- For textured and sensitive surfaces like wallpaper or plaster
- For objects up to 2kg\* per nail or 4kg using 2 nails
- Removable without a trace
- Reusable with a new strip

\*For optimal results please read instruction leaflet

- For textured and sensitive surfaces like wallpaper or plaster
- For objects up to 2kg\* per nail or 4kg using 2 nails
- Removable without a trace
- Reusable with a new strip

\*For optimal results please read instruction leaflet

## Application Fields

||

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                                |                  |                       |      |
|--------------------------------|------------------|-----------------------|------|
| • Type of adhesive             | synthetic rubber | • Holding power up to | 2 Kg |
| • Holding power of strip up to | 2 Kg             | • Silicone free       | yes  |



# tesa<sup>®</sup> Adhesive Nail for Wallpaper & Plaster 2kg

## Product Information

### Properties/Performance Values

• Application temperature from	-15 °C	• Residue free removal	yes
• Area of use	Indoor	• Reusable	yes
• Batteries included	no	• Reusable with	Adhesive Strip 1kg Wallpaper
• Batteries required	no	• Solvent free	yes
• Chemical resistance	no	• Suitable surfaces	Plaster, Wallpaper
• Hazard material	no	• Temperature resistance max.	35 °C
• Humidity resistance	no	• Temperature resistance min.	5 °C
• Material	PS (polystyrene)	• UV-resistant	no
• Oil and grease resistance	no	• Waterproof	no

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>