

# tesa<sup>®</sup> Adjustable Adhesive Screw for Wallpaper & Plaster 1kg



**Product Information** 

BNR 77775

## **Product Description**

Height adjustable Adhesive Screw for up to 1kg. Perfect for mounting decorative objects on textured and sensitive surfaces like wallpaper or plaster. Il Height adjustable Adhesive Screw for up to 1kg. Perfect for mounting decorative objects on textured and sensitive surfaces like wallpaper or plaster.

## **Product Features**

- · For textured and sensitive surfaces like wallpaper or plaster
- Holds up to 1kg\* per screw or 2kg using 2 screws
- Height adjustable for straight alignment
- Removable without a trace
- Reusable with a new strip

\*For optimal results please read instruction leafletll

- For textured and sensitive surfaces like wallpaper or plaster
- Holds up to 1kg\* per screw or 2kg using 2 screws
- Height adjustable for straight alignment
- Removable without a trace
- Reusable with a new strip

\*For optimal results please read instruction leaflet

### **Application Fields**

||

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### **Product Construction**

• Type of adhesive	synthetic rubber	Holding power of strip up to	1 Kg
Properties/Performance Values			
Application temperature from	-15 °C	Ozone resistance	no
<ul> <li>Chemical resistance</li> </ul>	no	<ul> <li>Residue free removal</li> </ul>	yes
<ul> <li>Hazard material</li> </ul>	no	Reusable	yes
<ul> <li>Humidity resistance</li> </ul>	no	<ul> <li>UV-resistant</li> </ul>	no
<ul> <li>Material</li> </ul>	PS (polystyrene)	Waterproof	no
Oil and grease resistance	no		



# tesa® Adjustable Adhesive Screw for Wallpaper & Plaster 1kg

**Product Information** 

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.