



tesa[®] PRO 74613 Duct Tape



Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------------|-------------------|--------|
| • Backing material | PE-film with PET-filament | • Total thickness | 175 µm |
| • Type of adhesive | synthetic rubber | | |

Product Assortment

- | | |
|--------------------|-------------|
| • Available colors | grey, black |
|--------------------|-------------|

Properties/Performance Values

- | | | | |
|--------------------------|--------------------------|-----------------------------|--------------|
| • Elongation at break | 14 % | • Oil and grease resistance | no |
| • Tensile strength | 40 N/cm | • Residue free removal | no |
| • Abrasion resistance | good | • Salt water resistance | medium |
| • Adhesive strength | High adhesion | • Solvent free | yes |
| • Ageing resistance (UV) | medium | • Straight tear edges | good, medium |
| • Automatic application | yes | • Tack | very good |
| • Chemical resistance | medium | • Tear resistance | yes |
| • Core diameter | 3 | • Temperature resistance | medium |
| • Easy to remove | no | • Tensibility | 14 % |
| • Easy to write on | no | • Transparency | no |
| • Hand tearability | good | • Unwind force n/cm | 3.5 N/cm |
| • Humidity resistance | medium | • Water resistance | low |
| • Low unwinding force | medium | • Waterproof | yes |
| • Manual application | yes | • Writable | no |
| • Mesh | 27 count per square inch | | |

Adhesion to Values

- | | | | |
|------------------|----------|---------|--------|
| • rough surfaces | 5.5 N/cm | • steel | 7 N/cm |
|------------------|----------|---------|--------|



tesa[®] PRO 74613 Duct Tape

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=74613>