

## tesa<sup>®</sup> Adjustable Adhesive Nail for Tiles & Metal 3kg



**Product Information** 

BNR 77764

#### **Product Description**

Height adjustable adhesive nail for up to 3kg. Perfect for hanging and aligning objects like kitchen utensils on smooth and solid surfaces like tiles and metal.llHeight adjustable adhesive nail for up to 3kg. Perfect for hanging and aligning objects like kitchen utensils on smooth and solid surfaces like tiles and metal.

### **Product Features**

- For smooth and solid surfaces like tiles indoors
- For objects up to 3kg per nail or 6kg using 2 nails
- Height adjustable for straight alignment of objects
- Removable without a trace
- Reusable with a new stripll\* For smooth and solid surfaces like tiles indoors
- For objects up to 3kg per nail or 6kg using 2 nails
- · Height adjustable for straight alignment of objects
- Removable without a trace
- Reusable with a new strip

#### **Application Fields**

||

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

- Type of adhesive
- synthetic rubber 3 Kg
- Holding power up to 3 KgSilicone free yes

- Holding power of strip up to
- Silicone free



# tesa<sup>®</sup> Adjustable Adhesive Nail for Tiles & Metal 3kg

**Product Information** 

## **Properties/Performance Values**

•	Application temperature from	-15 °C	Residue free removal	yes
•	Area of use	Indoor	Reusable	yes
•	Batteries included	no	<ul> <li>Reusable with</li> </ul>	Adhesive Strip
•	Batteries required	no		Tiles
•	Chemical resistance	no	Solvent free	yes
•	Hazard material	no	<ul> <li>Suitable surfaces</li> </ul>	Even wood, Tile
•	Humidity resistance	no		Most plastics, G
•	Material	PS (polystyrene)		Acrylic glass, St
•	Oil and grease resistance	no		Metal
•	Ozone resistance	no	• Temperature resistance max.	35 °C
			Temperature resistance min.	5 °C
			UV-resistant	no

Waterproof

o 3kg iles, Glass, Steel, no

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

