



# tesa® Powerbond Ultra Strong

## Product Information



BNR 55792, 55791

### Product Description

tesa Powerbond® Ultra Strong is the strongest mounting tape from tesa®. It is suitable for attaching objects indoors and outdoors. The impressive adhesive performance of up to 10 kg per 10 cm means that you can do without drills, plugs and screws even when fixing heavier objects. The mounting tape is easy to handle and provides a permanent and reliable hold.

### Product Features

- Ideal for indoor and outdoor\* use
- Ultra-strong hold
- Holds up to 10 kg\*\* per 10cm tape
- Holds on most smooth, sufficient firm surfaces

\*Not UV-resistant. Protect from direct contact with water.

\*\*For flat objects up to 10 mm thick

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                  |                               |          |
|--------------------|------------------|-------------------------------|----------|
| • Backing material | PE foam          | • Total thickness             | 1100 µm  |
| • Type of adhesive | synthetic rubber | • Holding power of tape up to | 100 KG/M |

### Properties/Performance Values

- |                                |                                                                                                 |                        |                                                                              |
|--------------------------------|-------------------------------------------------------------------------------------------------|------------------------|------------------------------------------------------------------------------|
| • Ageing resistance (UV)       | no                                                                                              | • Humidity resistance  | no                                                                           |
| • Application temperature from | -10 °C                                                                                          | • Residue free removal | no                                                                           |
| • Applicationfield             | Office, Garden,<br>Garage, Living room,<br>Children's room,<br>Home, Bedroom, Hall,<br>Bathroom | • Solvent free         | yes                                                                          |
|                                |                                                                                                 | • Suitable surfaces    | Even wood, Tiles,<br>Most plastics, Glass,<br>Acrylic glass, Steel,<br>Metal |
| • Chemical resistance          | no                                                                                              |                        |                                                                              |





# tesa® Powerbond Ultra Strong

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>