



# tesa<sup>®</sup> extra Power Extreme Repair

## Product Information



BNR 56064

### Product Description

tesa Extreme repair is a self-bonding Repairing Tape to be used as a non conductive electrical tape or a plumbers tape for temporary tube and pipe repairs.

### Product Features

- 12 bar pressure-resistant
- UV-resistant
- Temperature-resistant between -60°C to +260°C
- Withstands electricity of 8000V

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |          |                   |        |
|--------------------|----------|-------------------|--------|
| • Backing material | Silicone | • Total thickness | 500 µm |
|--------------------|----------|-------------------|--------|

### Properties/Performance Values

- |                                |                        |                          |  |
|--------------------------------|------------------------|--------------------------|--|
| • Tensile strength             | 33 N/cm                | • Residue free removal   | yes  |
| • Adhesive strength            | Very high adhesion     | • Solvent free           | yes  |
| • Ageing resistance (UV)       | yes                    | • Suitable surfaces      | Even wood, Tiles, Brick, Most plastics, Glass, Acrylic glass, Plaster, Metal, Steel, Stone |
| • Application temperature      | from -60°C up to 260°C |                          |  |
| • Application temperature from | -60 °C                 | • Tear resistance        | yes  |
| • Application temperature to   | +260 °C                | • Temperature resistance | yes  |
| • Area of use                  | Outdoor                | • Tensibility            | 750 %  |
| • Hand tearability             | no                     | • UV-resistant           | yes  |
| • Humidity resistance          | yes                    | • Water resistance       | yes  |
| • Oil and grease resistance    | yes                    | • Waterproof             | yes  |
| • Ozone resistance             | yes                    | • Writable               | no   |



# tesa<sup>®</sup> extra Power Extreme Repair

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>