



tesa® EasySplice 51150 FastLine



Product Information

Repulpable, double-sided splicing tape

Product Description

tesa® 51150 EasySplice FastLine is a repulpable double-sided integrated flying splice tape consisting of a flat-back paper and a modified water soluble acrylic adhesive

tesa® 51150 EasySplice FastLine features:

- Highest tack properties
- Very good adhesion values on coated and uncoated paper
- Low splice thickness
- Printable and coatable backing
- Good repulpability over pH-range: pH3 – pH9

Following functions are provided:

- Slit liner for the secure fixing of the top sheet
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- Two splitting strips with paper backing for a smooth opening of the new paper reel without affecting the coating process

Colour: Blue

Application Fields

tesa® 51150 EasySplice FastLine is particularly suitable for:

- Flying splices at fast running off-line coaters

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	flat paper	• Total thickness	100 µm
• Type of adhesive	repulpable tackified acrylic	• Colour	blue
• Type of liner	repulpable siliconised paper		

Properties/Performance Values

• Elongation at break	6 %	• Static shear resistance	medium
• Tensile strength	30 N/cm	• Tack	good
• Shelf life time (packed) < 25°C	12 months		

For latest information on this product please visit <http://l.tesa.com/?ip=51150>



tesa® EasySplice 51150 FastLine

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=51150>