


tesa® 58351

Product Information



tesa® 58351 is a 73 µm single-sided transparent PET filmic tape.

Product Description

The tackified acrylic adhesive gives this product a very good peel strength and outstanding anti-repulsion property. The 23µm transparent PET filmic backing offers excellent electrical insulation property. The glassine liner ensures it can be easily released without adhesive residue. It can meet the strict automotive environmental and long-term durability requirement.

Product Features

0

Application Fields

- Electrical insulation with anti-repulsion property

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PET	• Colour of liner	white/red logo
• Type of adhesive	tackified acrylic	• Thickness of liner	71 µm
• Type of liner	glassine	• Weight of liner	69 g/m ²
• Total thickness	73 µm		

Properties/Performance Values

• Breakdown voltage	6.5 KV	• Humidity resistance	very good
• Dielectric breakdown voltage	6500 V		

Adhesion to Values

• Aluminium (initial)	4.5 N/cm	• PC (after 14 days)	6 N/cm
• Aluminium (after 14 days)	6.3 N/cm	• Steel (initial)	5 N/cm
• PC (initial)	3.3 N/cm	• Steel (after 14 days)	7.9 N/cm

tesa® 58351

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=58351>