



tesa[®] 54951

Product Information



tesa[®] 54951

Product Description

tesa[®] 54951 is a double-sided segmented flying splicing tape (die-cuts on a roll) for melamine impregnated papers

It is particularly suitable for:

- overlay paper
- decorative paper
- balance paper

Application Fields

Customer Benefits

- One fits all – one tape for all different paper grades
- Secure splice performance without wrinkles and at high speeds
- Easy application due to segmented design

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|--------|
| • Backing material | Paper | • Total thickness | 105 µm |
| • Type of adhesive | water-based acrylic | • Colour | blue |
| • Type of liner | paper | • Colour of liner | white |

Properties/Performance Values

- | | | | |
|-----------------------------------|--------------|--------|-----------|
| • Shelf life time (packed) < 25°C | 12 months | • Tack | very good |
| • Static shear resistance | good, medium | | |

Adhesion to Values

- | | |
|-------------------|----------|
| • Steel (initial) | 3.5 N/cm |
|-------------------|----------|

Additional Information

High composite adhesion after splice for overlay paper

High composite adhesion after splice for decor paper

High composite adhesion after splice for balance paper

For latest information on this product please visit <http://l.tesa.com/?ip=54951>



tesa[®] 54951

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=54951>