

# tesa<sup>®</sup> EasySplice 51948 FilmLine Black X

**Product Information** 

tesa® 51948 EasySplice FilmLine Black X

## **Product Description**

tesa® EasySplice FilmLine Black X is an integrated flying splice tape consisting of a black PET backing and very high tack contact adhesive

tesa® 51948 EasySplice FilmLine Black X is particulary suitable for:

Flying splices in the flexography or rotogravure printing industry of flexible packaging material with high content of slip agents

## **Application Fields**

Main product feature

- · Very high tack contact adhesive
- Black PET backing
- Excellent wetting properties

Customer benefits:

- · Secure splicing performance on high slip films at high speeds
- Fast and easy splice preparation
- · Easy waste detection

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## **Product Construction**

<ul> <li>Backing material</li> </ul>	PET	Colour	black
<ul><li>Type of adhesive</li><li>Total thickness</li></ul>	synthetic rubber 115 μm	Colour of liner	white with tesa logo
Properties/Performance	e Values		
Tensile strength	70 N/cm	Static shear resistance	medium

•	ienslie strength	70 N/CIII
•	Shelf life time (packed) < 25°C	18 months

1,1	
3 3 3	
A STATE	

- Static shear resistance
- Tack

very good



# tesa® EasySplice 51948 FilmLine Black X

**Product Information** 

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.