




# tesa® 60744

## Product Information



tesa® 60744 50 µm thermal management tape

### Product Description

tesa® 60744 is a thermal management transfer tape which is designed for high thermal conductivity with strong mounting on heat source or heat spreading material such as display, MLB, and components in electronics devices.

### Product Features

- High thermal conductivity in z-direction
- Strong bonding strength
- Excellent surface wet-out
- Easy handling
- Thin design
- Excellent electrical insulation

### Application Fields

- Component mounting wherever heat transfer is needed
- Heat dissipation from MLB / FPC to heat spreader
- Display mounting and heat transfer to other substrate
- Vapor chamber or heat pipe mounting
- Antenna mounting
- Graphite sheet mounting

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |          |                   |             |
|--------------------|----------|-------------------|-------------|
| • Backing material | none     | • Total thickness | 50 µm       |
| • Type of adhesive | acrylic  | • Colour          | white       |
| • Type of liner    | PET film | • Colour of liner | transparent |

### Properties/Performance Values

- |                                    |        |           |      |
|------------------------------------|--------|-----------|------|
| • Breakdown voltage                | 2.9 KV | • Wetting | 84 % |
| • Thermal conductivity z-direction | 1 W/mK |           |      |

### Adhesion to Values

- |                   |        |
|-------------------|--------|
| • Steel (initial) | 5 N/cm |
|-------------------|--------|

For latest information on this product please visit <http://l.tesa.com/?ip=60744>



# tesa<sup>®</sup> 60744

## Product Information

### Additional Information

Thermal conductivity measured by ASTM D5470

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60744>