



# tesa® 54336

## flexible and temperature resistant



### Product Information

Precision die cuts for permanent hole covering applications with corrosion issue

### Product Description

tesa® 54336 is a strong PET with an extra thick adhesive layer. The product is optimised for the automotive industry to cover unused holes that require excellent sealing properties in combination with good temperature resistance.

Features:

- Ensures a reliable corrosion protection as e.g. the punch burrs will be securely sealed by 400µm adhesive layer
- Excellent temperature resistance up to 190°C extends the flexibility in the manufacturing process, e.g. PVC and/ or paint oven drying processes
- Good paint and UBC (PVC) compatibility
- Secure adhesion on painted substrates and on reinforced plastic substrates in automotive lightweight constructions

### Application Fields

tesa® 54336 is especially designed for interior and exterior hole covering applications at the assembly line or even at the paint shop area to protect exposed punch burrs against corrosion in combination with the freedom to decide when and where the holes are covered during the manufacturing process.

- After e-coat where a good compatibility to UBC (PVC) and sealant is required, e.g. car body platform, wheel houses, engine compartment
- Before paint shop where good paint compatibility is essential
- At the assembly line for exterior and interior Hole Covering on all car body areas, e.g. pillars, rocker, front/rear floor

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                  |                   |        |
|--------------------|------------------|-------------------|--------|
| • Backing material | PET              | • Total thickness | 450 µm |
| • Type of adhesive | modified acrylic | • Colour          | black  |
| • Type of liner    | PE-coated paper  |                   |        |

### Properties/Performance Values

- |                       |       |
|-----------------------|-------|
| • Puncture resistance | 440 N |
|-----------------------|-------|

### Additional Information

tesa® 54336 can be supplied as die cuts in roll or sheets individually to customer specific dimensions

tesa's automation and application solution department provides customized equipment and self-designed application tools to enhance productivity.

For latest information on this product please visit <http://l.tesa.com/?ip=54336>



# tesa® 54336

## flexible and temperature resistant

Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=54336>