




tesa® 60745

Product Information



tesa® 60745 100 µm thermal management tape

Product Description

tesa® 60745 is a transfer type of white thermal management transfer tape which is designed for excellent thermal conductivity with great mounting on heat source or heat spreading material such as 5G mmWave antenna, heat pipe and other components in electronics devices.

Product Features

- Excellent thermal conductivity in z-direction
- Good bonding strength
- Excellent surface wet-out
- Easy handling
- Thin design
- Excellent electrical insulation

Application Fields

- Component mounting wherever heat transfer is needed
- Heat dissipation from MLB / FPC to heat spreader
- Heat pipe mounting
- 5G mmWave antenna mounting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------|-------------------|-------------|
| • Backing material | none | • Total thickness | 100 µm |
| • Type of adhesive | acrylic | • Colour | white |
| • Type of liner | PET film | • Colour of liner | transparent |

Properties/Performance Values

- | | | | |
|------------------------------------|--------|-----------|------|
| • Breakdown voltage | 3.5 KV | • Wetting | 81 % |
| • Thermal conductivity z-direction | 1 W/mK | | |

Adhesion to Values

- | | |
|-------------------|----------|
| • Steel (initial) | 4.5 N/cm |
|-------------------|----------|



tesa® 60745

Product Information

Additional Information

Thermal conductivity measured by ASTM D5470

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60745>