



# 75530

## Product Information



ACX<sup>plus</sup> High Transparency 3000µm

### Product Description

tesa® ACX<sup>plus</sup> 75530 is a transparent acrylic core tape. It consists of a high-performance acrylic system and is primarily characterised by its Bonding Power, Stress Dissipation and its Temperature and Weather Resistance.

Due to the high transparency it is especially suitable for constructive bonding of transparent and translucent materials such as glass or acrylic.

The visco-elastic, solid acrylic core compensates different thermal elongation of bonded parts.

### Product Features

- Due to its thickness ideal for gap filling requirements

### Application Fields

Bonding of transparent and translucent materials in the following Industries:

- Partition Walls
- Sign manufacturing
- Deco Glass Panels

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |               |                   |             |
|--------------------|---------------|-------------------|-------------|
| • Backing material | solid acrylic | • Total thickness | 3000 µm     |
| • Type of adhesive | pure acrylic  | • Colour          | transparent |

### Adhesion to Values

- |                        |         |
|------------------------|---------|
| • Steel (after 3 days) | 30 N/cm |
|------------------------|---------|



# 75530

## Product Information

### Additional Information

PV 24 = Blue filmic liner

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=75530>