



tesa® 64280

Product Information



Flexible transport securing tape with PET backing

Product Description

tesa® 64280 combines a secure bond to various substrates with the flexibility of a polyester backing.

A new polyester backing design makes it possible to significantly increase the tensile strength and to reduce the risk of tearing.

Due to its outstanding conformability the product is ideally suited for applications on “3-dimensional” surfaces.

tesa® 64280 can be removed residue- and discoloration-free from a variety of different surfaces.

Application Fields

Transport securing of appliances and office automation equipment such as printers, scanners, copying machines. Also suited for temporary surface protection and logo covering.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing material | PET | • Total thickness | 60 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|----------|------------------------|-----|
| • Elongation at break | 30 % | • No discolouration | yes |
| • Tensile strength | 140 N/cm | • Residue free removal | yes |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 4 N/cm |
|---------|--------|



tesa[®] 64280

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64280>