



tesa®

## Product Information

BNR 55485

### Product Description

tesa® PE Plastering Tape is a high-quality tape, perfect for outdoor applications. It is highly protective as it keeps surfaces safe from dirt or damage and sticks even on slightly rough surfaces. The tape is made of excellent quality materials and offers tough protection, for example, of frames and facades during the plastering.

No traces are left behind and with excellent UV-resistance for up to 12 weeks. Achieve great looks and high-quality results with tesa® PE Plastering Tape.

### Product Features

- Ideal for high-quality outdoor applications and plastering, sticks well to rough surfaces
- Permanent use - long-term application, UV-sunlight protection up to 12 weeks
- High-quality, robust PE backing material
- Made to last: Can be applied in a wide temperature range and is heat- and cold-resistant
- Residue-free removal for up to 12 weeks
- Good application to rough surfaces, easily removable without losing its shape when pulled
- Convenient to use: The tape is easy to unwind and hand-tearable

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |         |                   |        |
|--------------------|---------|-------------------|--------|
| • Backing material | PE      | • Total thickness | 120 µm |
| • Type of adhesive | acrylic |                   |        |

### Properties/Performance Values

- |                    |         |                |     |
|--------------------|---------|----------------|-----|
| • Tensile strength | 15 N/cm | • UV-resistant | yes |
|--------------------|---------|----------------|-----|

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>