



tesa[®] Professional

Product Information

BNR 56270, 56271, 56212, 56299, 56245

Product Description

tesa[®] Masking Tape Professional, our best masking tape to date. The Washi tape paper quality guarantees accuracy for razor-sharp and flat paint edges every time. Thanks to its versatility and tear-resistance properties, it adheres well to a variety of surfaces and is easy to remove.

No traces are left behind, with excellent residue-free removal for up to 6 months indoors and up to 2 months outdoors. Achieve professional high-quality results with tesa[®] Masking Tape Professional.

Product Features

- For high quality masking paint jobs - get expert quality results
- Original Washi Paper - for excellent and accurate sharp paint edges
- Residue-free removal for up to 6 months indoors and 2 months outdoors
- Flexible: Adapts well to a variety of surfaces - made for indoor and outdoor painting projects
- Suitable for all paints, lacquers, varnishes and glazes
- Easy to use: tesa[®] Masking Tape Professional is extra-tear-resistant
- Avoid using masking tape directly on wooden floors

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------|-------------------|-------|
| • Backing material | flat paper | • Total thickness | 90 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|----------------------|-----------------|----------------------|-----|
| • Tensile strength | 30 N/cm | • Batteries required | no |
| • Applicationfield | Home | • Hand tearability | yes |
| • Area of use | In- and Outdoor | • Tear resistance | yes |
| • Batteries included | no | | |



tesa[®] Professional

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>