



# tesamoll® STANDARD Door-to-floor Brush

## Product Information

BNR 05433

## Product Description

tesamoll® STANDARD Door-to-floor Brush is a highly effective self-adhesive draught excluder brush. It keeps cold air out and is able to seal gaps up to 12 mm.

## Product Features

- Suitable for smooth floor surfaces like parquet and wooden floors, PVC, laminate
- For gaps of up to 12mm
- Easy self-adhesive fitting without screws or nails
- Durability: 4 years
- UV-resistant
- Abrasion-resistant
- Long-lasting and durable
- Material: plastic

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- Type of adhesive acrylic
- Gap coverage up to 12 mm

## Properties/Performance Values

- |                       |            |                        |   |
|-----------------------|------------|------------------------|---|
| • Applicationfield    | Home, Door | • Material             | PP (polypropylene), PET (Polyethylene terephthalate), Plastic |
| • Batteries included  | no         | • Residue free removal | no  |
| • Batteries required  | no         | • Solvent free         | yes   |
| • Chemical resistance | no         | • Suitable surfaces    | Wooden floors   |
| • Durability          | 4 years    |                        |   |



# tesamoll<sup>®</sup> STANDARD Door-to-floor Brush

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>