

# tesa® Elegaant glass shelf, self-adhesive, chromed metal, unique design

# **Product Information**



BNR 40442

# **Product Description**

The lean, cultivated look of the tesa® Elegaant glass shelf makes it a unique storage solution. Moreover, it is applied with adhesive rather than drilling. Thus, walls and tiles remain untouched. The shelf can be removed cleanly at any time and moved to another position with a new adapter BK20-2. IThe lean, cultivated look of the tesa® Elegaant glass shelf makes it a unique storage solution. Moreover, it is applied with adhesive rather than drilling. Thus, walls and tiles remain untouched. The shelf can be removed cleanly at any time and moved to another position with a new adapter BK20-2.

### **Product Features**

- Robust glass shelf, including the tesa® Power.Kit technology (the all-in-one adhesive mounting solution)
- Extraordinary design, smoothed angular style, high gloss chrome-plated metal, smoothed square wall plates, white frosted glass
- Secure hold, waterproof, guaranteed stainless
- · Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- · Does not work on wallpaper, stucco and other surfaces with non-stick coating
- · Can be taken off without a trace or surface damage. Can be re-attached with adapter BK20-2
- · Clean, simple mounting without drilling
- Product dimensions: 50mm x 600mm x 123mmll\* Robust glass shelf, including the tesa® Power.Kit technology (the all-in-one adhesive mounting solution)
- Extraordinary design, smoothed angular style, high gloss chrome-plated metal, smoothed square wall plates, white frosted glass
- Secure hold, waterproof, guaranteed stainless
- · Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- · Does not work on wallpaper, stucco and other surfaces with non-stick coating
- · Can be taken off without a trace or surface damage. Can be re-attached with adapter BK20-2
- · Clean, simple mounting without drilling
- Product dimensions: 50mm x 600mm x 123mm

### **Application Fields**

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## **Product Construction**

• Type of adhesive Silane modified • Holding power up to 6 Kg polymer



# tesa® Elegaant glass shelf, self-adhesive, chromed metal, unique design

# **Product Information**

# **Properties/Performance Values**

| • | Applicationfield    | Bathroom       | • | Residue free removal | yes                  |
|---|---------------------|----------------|---|----------------------|----------------------|
| • | Chemical resistance | no             | • | Reusable             | yes                  |
| • | Curing time         | 12 hour(s)     | • | Reusable with        | Adapter BK20-2       |
| • | Design series       | tesa® ELEGAANT | • | Shape of wall piece  | Rounded edges        |
| • | Hazard material     | yes            | • | Solvent free         | yes                  |
| • | Humidity resistance | yes            | • | Suitable surfaces    | Glazed Tiles, Even   |
| • | Material            | Chromed metal, |   |                      | wood, Most plastics, |
|   |                     | Frosted glass  |   |                      | Glass, Concrete,     |
|   |                     |                |   |                      | Metal, Marble, Stone |
|   |                     |                | • | UV-resistant         | yes                  |
|   |                     |                |   |                      |                      |

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

