

# tesa® Aluminium tape

**Product Information** 



BNR 56223

### **Product Description**

tesa® Aluminium tape is a multi-use self-adhesive tape perfectly suited to quickly repair any metal surface, such as heating appliences, ducts or gutters.

#### **Product Features**

- Suitable for protecting, covering, insulating and repairing \* May also be used for roof and gutter repairs and sealing of ducts \* Temperature resistant from -40°C to +140°C \* Water, oil and grease-resistant
- Age-resistant \* High adhesive strength

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

| <ul><li>Backing material</li><li>Type of adhesive</li></ul> | aluminium foil<br>acrylic | Total thickness        | 100 µm              |
|---|---------------------------|------------------------|---------------------|
| Properties/Performance Values                               |                           |                        |                     |
| Tensile strength  | 15 N/cm                   | Suitable surfaces      | Glass, Metal, Steel |
| Abrasion resistance   | no                        | Temperature resistance | yes                 |
| Adhesive strength   | High adhesion             | Tensibility            | 5 %                 |
| Area of use   | In- and Outdoor           | UV-resistant           | yes                 |
| <ul> <li>Humidity resistance</li> </ul>                     | yes                       | Waterproof             | yes                 |
| <ul> <li>Oil and grease resistance</li> </ul>               | yes                       | Writable               | no                  |
| Residue free removal  | no                        |                        |                     |

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.