



tesa® Residue-free Removal

Product Information



BNR 55735, 55731, 55729

Product Description

tesa® Flooring Tape Residue-free Removal is a double-sided self-adhesive carpet and PVC flooring tape that is textile reinforced and allows residue free removal

Product Features

- For fixation of all carpet and PVC flooring materials
- Sticks to many types of floor and is removable without leaving residue*
- Double-sided adhesive
- Textile reinforced
- Easy to tear by hand

*Application notice: Not suitable for natural stone floors

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|--------|
| • Type of adhesive | tackified acrylic | • Total thickness | 248 µm |
|--------------------|-------------------|-------------------|--------|

Properties/Performance Values

- | | | | |
|------------------------|--------------------|--------------------------|--|
| • Tensile strength | 30 N/cm | • Solvent free | yes |
| • Adhesive strength | Very high adhesion | • Suitable surfaces | Tiles, Wooden floors, Brick, Most plastics, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone |
| • Chemical resistance | yes | | |
| • Material | PP (polypropylene) | | |
| • Residue free removal | yes | | |
| | | • Temperature resistance | yes |
| | | • Tensibility | 80 % |



tesa® Residue-free Removal

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>