



tesafilm® eco & clear

Product Information

BNR 57046, 04112, 56997, 57070, 57074, 57043, 57035, 57049, 57969, 57069, 57968

Product Description

tesafilm® eco & clear, a 100% recycled self-adhesive transparent tape, environment friendly

Product Features

- Film and core made from 100% recycled plastic
- Solvent free adhesives
- Transparent clear quality
- Almost invisible on many surfaces
- High age-resistance
- Silent unwinding
- Packaging: 80% recycled cardboard
- Suitable for use in all available tesafilm® dispensers
- The recycled content has been approved by the independent certification organization DIN CERTCO belonging to the TÜV Rheinland (German technical control board).

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing material | BOPP | • Total thickness | 52 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|---------------------|------------------|
| • Elongation at break | 20 % | • Solvent free | yes |
| • Tensile strength | 50 N/cm | • Suitable surfaces | Cardboard, Paper |
| • Ageing resistance (UV) | yes | • Tear resistance | no |
| • Hand tearability | no | • Transparency | good |
| • Low noise unwinding | yes | • Unwind force n/cm | 2.6 N/cm |
| • Photocopy neutral | yes | • Writable | no |



tesafilm® eco & clear

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>