



tesapack[®] eco & ultra strong ecoLogo[®]



Product Information

BNR 58297, 58299

Product Description

tesapack[®] ECO & ULTRA STRONG ecoLogo[®] is a high-performing packaging tape based on 90% Post-Consumer Recycled PET content in backing and a very strong waterborne acrylic adhesive. tesapack[®] ECO & ULTRA STRONG ecoLogo[®] is the ideal solution for medium- and heavy-weight packaging applications up to 30 kg.

Product Features

- tesa[®] recycled PET packaging tape
- Sustainable (recycling-friendly tape / solvent-free)
- Ideal for medium- and heavy-weight packaging applications up to 30 kg
- A strong and very consistent acrylic adhesive
- Very good performance on recycled cardboards
- 90% Post-Consumer Recycled PET content in backing
- Recycle-friendly according to INGEDE method 12

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------------|-------------------|-------|
| • Backing material | Post consumer recycled PET | • Total thickness | 56 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------------|-----------------------|------------------|
| • Elongation at break | 100 % | • Low noise unwinding | yes |
| • Tensile strength | 60 N/cm | • Solvent free | yes |
| • Adhesive strength | High adhesion | • Suitable surfaces | Cardboard, Paper |
| • Ageing resistance (UV) | yes | • Tear resistance | yes |
| • Hand tearability | no | • Unwind force n/cm | 5 N/cm |



tesapack[®] eco & ultra strong ecoLogo[®]

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>