



tesa®

Product Information

BNR 56250, 56214, 56251

Product Description

The paper-based tesa® Masking Tape Professional is both weather and UV-resistant and offers extremely precise paint edges.

Product Features

- For slightly uneven surfaces
- Residue-free removal for up to 8 weeks outdoors
- Solvent-free
- Weather- and UV-resistant
- For prestigious painting jobs which have to be exact and precise
- Suitable for most paints
- Avoid using masking tape directly on wooden floors

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------|-------------------|-------|
| • Backing material | flat paper | • Total thickness | 90 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------------------|---------|-------------------|-----|
| • Tensile strength | 30 N/cm | • Tear resistance | yes |
| • Area of use | Outdoor | • UV-resistant | yes |
| • Residue-free removable after... | 60 days | | |
| days | | | |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>