

tesa® EXXCELLENT Robe Hook, Self-Adhesive, Chromed Metal

Product Information

BNR 40471

Product Description

Gorgeously made and offering a space-saving two hooks, the timeless tesa® Exxcellent robe hook also has a splendid round design. The hook is applied with an adhesive solution rather than drilling. Surfaces remain unharmed. You can remove the hook cleanly and reuse it elsewhere with a new adapter BK20.

Product Features

- Sturdy robe hook, including the tesa® Power.Kit technology (the all-in-one adhesive mounting solution)
- Timeless design, round style, high gloss chrome-plated metal, circular wall plate
- · Reliable hold, waterproof, guaranteed stainless
- · Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- · Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Can be taken down without a trace or surface damage and put up again with adapter BK20
- · Effortless, clean application without drilling
- Product dimensions: 50mm x 75mm x 62mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	Silane modified	•	Hook shape	Round
		polymer			

Holding power up to
6 Kg

Properties/Performance Values

•	Applicationfield	Bathroom	•	Number of hooks	Double
•	Area of use	Indoor	•	Residue-free removability	yes
•	Batteries included	no	•	Reusable	yes
•	Batteries required	no	•	Reusable with	Adapter BK20
•	Chemical Resistance	no	•	Shape of wall piece	Round
•	Curing time	12 hour(s)	•	Solvent free	yes
•	Design series	tesa® EXXCELLENT	•	Suitable surfaces	Glazed Tiles, Marble,
•	Humidity resistance	yes			Glass, Metal, Stone,
•	Material	Chromed metal			Concrete, Even wood,

Most plasticsUV resistantWaterproofyes



tesa® EXXCELLENT Robe Hook, Self-Adhesive, Chromed Metal

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

