



tesa[®] 60454

Product Information

Masking tape

Product Description

tesa[®] 60454 is a filmic masking tape to be used to mask glass and metal during etching. To achieve sharp definition of colour edges tesa[®] 60454 is also used for multi-colour painting purposes.

Product Features

- This product withstands diluted acids and alkalis.

Application Fields

- Masking tape for wide range of masking requirements
- Masking tape to be used for multicolor painting purposes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing material | PVC film | • Total thickness | 65 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|------------------|-----|
| • Elongation at break | 78 % | • Easy to remove | yes |
| • Tensile strength | 43 N/cm | | |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 3 N/cm |
|---------|--------|



tesa® 60454

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60454>