



tesa® Adhesive Strips for Tiles & Metal 2kg



Product Information

BNR 77760

Product Description

Refill pack for the Adhesive Nail for Tiles & Metal 2kg. For convenient reuse of the Adhesive Nail or to use alone. II Refill pack for the Adhesive Nail for Tiles & Metal 2kg. For convenient reuse of the Adhesive Nail or to use alone.

Product Features

- Strip for reuse of the Adhesive Nail for Tiles & Metal 2kg
- For smooth and solid surfaces like tiles indoors
- For objects up to 2kg per strip
- Strip can also be used alone without a nail
- Removable without a trace II Strip for reuse of the Adhesive Nail for Tiles & Metal 2kg
- For smooth and solid surfaces like tiles indoors
- For objects up to 2kg per strip
- Strip can also be used alone without a nail
- Removable without a trace

Application Fields

- How to apply – Step by step I. To ensure the best possible bond, clean the surface with a silicone-free window cleaner or methylated spirit. The surface should be completely dry before application.
1. The Adhesive Strip should be applied to the rougher surface. Be careful not to touch the exposed adhesive area at any time.
 2. Press down evenly over the entire strip for at least 5 seconds and then remove the protective foil.
 3. Now apply your object or a tesa® Adhesive Nail by aligning it on the top edge of the strip and then folding it down. Press down evenly all over your entire object or the entire nail for at least another 5 seconds.
 4. The tab should be left accessible behind your object or beneath the nail for easy removal.

- II How to apply – Step by step I. To ensure the best possible bond, clean the surface with a silicone-free window cleaner or methylated spirit. The surface should be completely dry before application.
1. The Adhesive Strip should be applied to the rougher surface. Be careful not to touch the exposed adhesive area at any time.
 2. Press down evenly over the entire strip for at least 5 seconds and then remove the protective foil.
 3. Now apply your object or a tesa® Adhesive Nail by aligning it on the top edge of the strip and then folding it down. Press down evenly all over your entire object or the entire nail for at least another 5 seconds.
 4. The tab should be left accessible behind your object or beneath the nail for easy removal.



tesa[®] Adhesive Strips for Tiles & Metal

2kg

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|--------------------------------|------|
| • Type of adhesive | synthetic rubber | • Holding power of strip up to | 2 Kg |
| • Total thickness | 650 µm | | |

Properties/Performance Values

- | | | | |
|--------------------------------|-------------------|------------------------|-----|
| • Application temperature from | -15 °C | • Ozone resistance | no |
| • Chemical resistance | no | • Residue free removal | yes |
| • Hazard material | no | • Solvent free | yes |
| • Humidity resistance | no | • UV-resistant | no |
| • Material | PE (polyethylene) | • Waterproof | no |
| • Oil and grease resistance | no | | |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>