

tesa[®] Powerstrips Cable Clip

Product Information



BNR 58035, 64364

Product Description

Use self-adhesive tesa Powerstrips Cable-Clips to run cables unobtrusively. They stick to just about any flat surface and come off easily to be reused anytime. Il Use self-adhesive tesa Powerstrips Cable-Clips to run cables unobtrusively. They stick to just about any flat surface and come off easily to be reused anytime.

Product Features

- · Easy to mount without drilling, screws or nails
- Easy to fix cables of up to 8mm diameter
- Removable without trace thanks to the Powerstrips technology
- Brings order where there is cable chaos
- Clip is reusable with tesa Powerstrip Small
- Cable-clip covers tesa Powerstrip completelyll* Easy to mount without drilling, screws or nails
- Easy to fix cables of up to 8mm diameter
- Removable without trace thanks to the Powerstrips technology
- Brings order where there is cable chaos
- Clip is reusable with tesa Powerstrip Small
- Cable-clip covers tesa Powerstrip completely

Application Fields

How to apply - Step by step 1. Clean the surface with alcohol or silicone-free glass cleaner

- 2. Apply the Powerstrip Small strip on the surface press for 5 seconds minimum
- 3. Open the cable clip and stick the back of the clip onto the strip press for 5 seconds minimum
- 4. Close and snap-lock the clip
- $\ensuremath{\mathsf{IHow}}$ to apply Step by step 1. Clean the surface with alcohol or silicone-free glass cleaner
- 2. Apply the Powerstrip Small strip on the surface press for 5 seconds minimum
- 3. Open the cable clip and stick the back of the clip onto the strip press for 5 seconds minimum
- 4. Close and snap-lock the clip

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	synthetic rubber	•	Hook shape	Rectangular
•	Holding power up to	1 Kg	•	Silicone free	yes



tesa® Powerstrips Cable Clip

Product Information

Properties/Performance Values

Application temperature from -15 °	C •	Ozone resistance
Applicationfield Office	ce, Kitchen, Living •	Residue free removal
roor	n, Children's •	Reusable
roor	n, Hall, Bathroom 🔹	Solvent free
Chemical resistance no	•	Temperature resistance
Hazard material no	•	UV-resistant
Humidity resistance no	•	Waterproof
• Material PS (polystyrene)	
Oil and grease resistance no		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

yes

yes yes yes

yes no no