



tesa® 4333 Precision Mask® Sensitive



Product Information

High grade Washi masking tape for precise and flat paint edges on sensitive surfaces

Product Description

The Washi masking tape tesa Precision Mask® 4333 is perfectly suited for painting work on sensitive surfaces such as wall coverings, wallpaper and varnished surfaces. As a professional masking tape it is extremely gentle yet still sticks firmly. Therefore it prevents paint tears without damaging the surface. This innovative professional masking tape comprises a tear-proof, extremely thin special backing which is coated with an acrylate adhesive compound and is particularly easy to use. This new masking tape was developed especially for applications where maximum precision is vital.

Product Features

- This tape is suited for almost all indoor paint works
- tesa® 4333 PV1 Precision Mask® Sensitive is applicable with water-based paints and lacquers and fits even for high-class spatula techniques
- It is especially designed for applications on sensitive and critical surfaces
- The flat backing material is highly conformable to the surface and leads to precise razor-sharp paint edges

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------|-------------------|-------|
| • Backing material | Washi paper | • Total thickness | 85 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|------------------------|-----------|-----------------------------------|-----------|
| • Elongation at break | 4.5 % | • Residue-free removable after... | 14 days |
| • Tensile strength | 41 N/cm | • Sharp colour edge | very good |
| • Hand tearability | very good | • Solvent free | yes |
| • Residue free removal | yes | | |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 0.6 N/cm |
|---------|----------|



tesa[®] 4333 Precision Mask[®] Sensitive

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=04333>