



tesa® Powerstrips Hooks S metal rectangular



Product Information

BNR 57066

Product Description

Small self-adhesive metal bathroom and kitchen hook for traceless removal

||

Small self-adhesive metal bathroom and kitchen hook for traceless removal

Product Features

- Easy to mount without drilling, screws or nails
- Strong hold up to 1kg
- Removable without a trace thanks to the Powerstrips technology
- High quality design, brushed stainless steel
- Usable on tiles, glass, wood, plastic and a variety of other smooth surfaces*
- Hooks reusable with tesa Powerstrips Small

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

||

- Easy to mount without drilling, screws or nails
- Strong hold up to 1kg
- Removable without a trace thanks to the Powerstrips technology
- High quality design, brushed stainless steel
- Usable on tiles, glass, wood, plastic and a variety of other smooth surfaces*
- Hooks reusable with tesa Powerstrips Small

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

Application Fields

||

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|------------------|--------------|-------------|
| • Type of adhesive | synthetic rubber | • Hook shape | Rectangular |
| • Holding power up to | 1 Kg | | |



tesa® Powerstrips Hooks S metal rectangular

Product Information

Properties/Performance Values

• Application temperature	from 20°C up to 25°C	• Ozone resistance	no
• Application temperature from	+15 °C	• Residue free removal	yes
• Application temperature to	+35 °C	• Reusable	yes
• Applicationfield	Bathroom, Kitchen	• Reusable with	Powerstrips Small
• Chemical resistance	no	• Solvent free	yes
• Hazard material	no	• Temperature resistance	yes
• Material	Stainless steel, Plastic	• UV-resistant	no
• Oil and grease resistance	no		

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>