



# tesa® Professional 4435

## Product Information

### UV resistant paper tape

#### Product Description

tesa® 4435 is a slightly creped UV resistant masking tape consisting a substrate coated with a natural rubber adhesive mass. The masking tape has a balanced adhesive strength. It is easy to use and can be torn by hand. It is particularly well suited to outdoor painting tasks – including on rough surfaces – and can be used for up to 2 weeks, thanks to its UV resistance. tesa® 4435 is the ideal basis for professional and precise painting work.

#### Product Features

- Outdoor applications (up to 2 weeks)
- Painting and lacquering work
- Suitable on a variety of common surfaces

\*The application of an adhesive tape on weathered surfaces may lead to residues during the de-masking. Therefore we strongly recommend a test application before.

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Product Construction

- |                    |                       |                   |        |
|--------------------|-----------------------|-------------------|--------|
| • Backing material | slightly-creped paper | • Total thickness | 145 µm |
| • Type of adhesive | natural rubber        |                   |        |

#### Properties/Performance Values

- |                       |         |                    |      |
|-----------------------|---------|--------------------|------|
| • Elongation at break | 12 %    | • Hand tearability | good |
| • Tensile strength    | 38 N/cm |                    |      |

#### Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 2.8 N/cm |
|---------|----------|



# tesa® Professional 4435

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?mp=04435>