



# tesa<sup>®</sup> extra Power Universal >60% Recycled Plastic

## Product Information

BNR 56348, 56396, 56389, 56490, 56388

## Product Description

Sustainability without compromise: tesa<sup>®</sup> Extra Power Universal Repairing Tape is made from 67% recycled materials. This adhesive tape retains a reliable performance and is suitable for various applications.

## Product Features

- Environmentally conscious: The backing is made from 67% recycled content and sustainable packaging
- Strong hold: The repairing tape sticks firmly and reliably even to very rough surfaces
- Easy to use: The tape can be conveniently torn by hand, making it ready for use
- Weather-ready: The waterproof, weather-resistant tape offers a strong hold both indoors and outdoors
- Versatile all-rounder: Ideal for DIY projects, fixing, sealing or repairs
- Scope of delivery: 1 x roll of tesa<sup>®</sup> extra Power Universal Multi-purpose Duct Tape

## Application Fields

- Environmentally conscious: The backing is made from 67% recycled content and sustainable packaging
- Strong hold: The repairing tape sticks firmly and reliably even to very rough surfaces
- Easy to use: The tape can be conveniently torn by hand, making it ready for use
- Weather-ready: The waterproof, weather-resistant tape offers a strong hold both indoors and outdoors
- Versatile all-rounder: Ideal for DIY projects, fixing, sealing or repairs
- Scope of delivery: 1 x roll of tesa<sup>®</sup> extra Power Universal Multi-purpose Duct Tape

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |   |                    |                    |                  |
|---|--------------------|--------------------|------------------|
| • Backing material                                      | PE laminated cloth | • Type of adhesive | synthetic rubber |
| • Bio-based carbon content of liner (acc. DIN EN 16640) | 67 %               | • Total thickness  | 215 µm           |



# tesa<sup>®</sup> extra Power Universal >60% Recycled Plastic

## Product Information

### Properties/Performance Values

• Elongation at break	16 %	• Hand tearability	good
• Tensile strength	41.2 N/cm	• Humidity resistance	yes
• Abrasion resistance	very good	• Residue free removal	no
• Adhesive strength	High adhesion	• Solvent free	yes
• Ageing resistance (UV)	yes	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Metal
• Application temperature from	5 °C		
• Application temperature to	60 °C		
• Area of use	In- and Outdoor	• Tear resistance	yes
• Chemical resistance	yes	• UV-resistant	yes
• Ecofriendly packaging	yes	• Waterproof	yes
		• Writable	yes

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>