



tesa® Professional 53949 Matt Gaffer Tape 80 Mesh

Product Information

Light-absorbing fabric tapes for many kinds of uses at events

Product Description

Our fabric tape tesa® 53949 consists of a PE-extruded fabric fitted with an adhesive made from natural rubber. As it is available in 3 matt product variants, it is particularly well suited for applications when reflections have to be avoided. The multi-purpose fabric tape sees frequent use at events of all kinds, e.g. at concerts, trade fairs or theater performances. The fabric tape provides a good adhesive strength (even on rough surfaces), is light-absorbing, can be torn off by hand and can be removed effortlessly. Furthermore, it is abrasion-proof, smooth, flexible, water-repellent and weather-proof so that it is well suited for outdoor applications.

Product Features

- Indoors and outdoors
- Ideal for events of all kinds (theater, opera, concerts, trade fairs)
- On stage and backstage
- To cover glossy, reflecting surfaces
- Temporary fixation, e.g. cables or carpets
- Taping over of gaps and joints
- Floor markings, e.g. position marks

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|--------|
| • Backing material | PE extruded cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|-----------------------|------|
| • Elongation at break | 14 % | • Hand tearability | good |
| • Tensile strength | 85 N/cm | • Humidity resistance | good |
| • Abrasion resistance | good | • Water resistance | good |
| • Ageing resistance (UV) | good | | |



tesa® Professional 53949 Matt Gaffer Tape 80 Mesh

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=53949>