



tesa[®] Professional 4405 Easy Cover[®] Standard Paper

Product Information

2-in-1 masking (masking paper & painter's tape)

Product Description

tesa Easy Cover[®] Standard Paper is a covering solution saving time and money for professional painters. Thanks to the integrated painter's tape, you can cover large areas and precisely tape off edges in just one step. The masking paper can be applied securely, providing clean paint edges indoors. It is suited not only for traditional paint jobs but also for spray techniques. In particular masking and protecting windows and doors becomes child's play.

Product Features

- Time-saving 2-in-1 covering solution for professionals: covering large areas and precise masking in one step
- Combination of masking paper and integrated tesa[®] painter's tape
- For clean paint edges indoors
- Applicable on smooth surfaces
- Ideal to tape off baseboards, window sills or door frames

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing material | slightly-creped paper | • Total thickness | 120 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------------|---------|-------------------------------|--------|
| • Tensile strength | 35 N/cm | • Suitable for rough surfaces | medium |
| • Material of masking coverage | paper | | |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 3 N/cm |
|---------|--------|



tesa[®] Professional 4405 Easy Cover[®] Standard Paper

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?mp=04405>