

# tesa® 4563

# **Product Information**



Silicone rubber coated fabric tape with outstanding grip properties

## **Product Description**

tesa® 4563 consists of a specially treated fabric covered with a silicone rubber coating. This surface is highly resistant to "sticky" substances yet provides a reliable "non-slip" effect on smooth substrates. Non-slip properties are maximized by the smooth surface.

## **Application Fields**

tesa® 4563 is specially designed for roller wrapping applications. In many cases, a new covering may be applied without removing the roller from the machine.

Industries include:

- \*Printing industry
- \*Textiles industry
- \*"Focus" label printing machinery

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

• Backing material Silicone-coated cloth • Total thickness 380 µm

Type of adhesive natural rubber

#### **Additional Information**

The product's shelf life is 12 months.

4563 PV2 - Here the only difference compared to the PV0 is the adhesion to steel of 3,2N/cm

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

<sup>\*</sup>General, web-based processing & converting industries