



# tesa® Professional 4373 UV

## Product Information

2-in-1: Paint masking film with special outdoor cloth tape

## Product Description

What makes tesa Easy Cover® Extra Strong so special is its sturdiness, because the sturdy paint masking film and the highly adhesive tesa® 4370 UV fabric tape provide safe protection. The paint masking film and surface protection tape withstand any weather and even the coarsest of dirt. Thus, the time-saving 2-in-1 solution is also suitable for plastering, and all kinds of rendering work, as well as painting, for a time period of maximum 8 weeks. This extremely high-strength paint masking film combines a tough, environmentally friendly PE film with a UV-resistant, highly adhesive masking tape. This allows you to cover paint edges and the surfaces of windows or furniture in only one working step, saving you both time and money. And thanks to the superior tesa quality, you also avoid touching-up work, which causes further costs. The paint masking film with integrated masking tape combined with your skilled workmanship provides an optimum basis for outstanding painting work which will leave your customers extremely impressed.

## Product Features

- Outdoor masking
- The 2-in-1 solution for masking off and protecting large areas \* For clean, straight paint edges
- For smooth and slightly rough surfaces
- Ideal for covering windows during rendering, plastering and painting work
- For heavy-duty, long-term applications

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing material | cloth          | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber |                   |        |

## Properties/Performance Values

- |                       |         |                                |           |
|-----------------------|---------|--------------------------------|-----------|
| • Elongation at break | 10 %    | • Material of masking coverage | LDPE      |
| • Tensile strength    | 60 N/cm | • Suitable for rough surfaces  | very good |

## Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 3.8 N/cm |
|---------|----------|



# tesa® Professional 4373 UV

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?mp=04373>