



tesa® Professional 4403 Easy Cover® Standard

Product Information

Slightly creped painter's tape with masking film

Product Description

tesa Easy Cover® Standard is a covering solution allowing professional painters to save time and money. Due to the integrated painter's tape, you can cover large areas and precisely tape them off in just one step. The robust masking film can be applied securely and accurately, creating clean paint edges indoors. It is also suited not only for traditional paint jobs but also for spray techniques. Especially covering furniture, floors and walls becomes child's play.

Product Features

- Time-saving 2-in-1 covering solution for professionals: covering large areas with masking in one step
- Combination of masking film and integrated slightly creped tesa® painter's tape
- For clean paint edges indoors
- Applicable on smooth, slightly structured and sensitive surfaces
- Ideal for covering furniture, floors and walls

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing material | slightly-creped paper | • Total thickness | 120 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------------|--------|
| • Elongation at break | 9 % | • Suitable for rough surfaces | medium |
| • Tensile strength | 35 N/cm | | |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 3 N/cm |
|---------|--------|



tesa® Professional 4403 Easy Cover® Standard

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?mp=04403>