



# tesa® 74921

## Self-adhesive Protection Film

### Product Information

tesa® Self-adhesive Protection Film - Glass - For large area protection and coverage of various plain surfaces

### Product Description

The self-adhesive film is ideal for large-area protection of glass and multiple other plain surfaces. It offers effective protection against any kind of spills and dirt. It also protects from scratches on various smooth surfaces such as windows, window frames, mirrors and glass doors. It is easy to apply and remove without leaving adhesive residues for up to 6 months, which makes clean-up hassle-free.

### Product Features

- Easy application
- Protects against any concrete and paint spills, dirt, dust, scratches and stains
- Clean removal without leaving any residue for up to 6 months
- Repositionable multiple times
- Smooth and thin PE film

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                     |                   |       |
|--------------------|---------------------|-------------------|-------|
| • Backing          | PE film             | • Total thickness | 35 µm |
| • Type of adhesive | water-based acrylic |                   |       |

### Properties/Performance Values

- |                                |                     |                                   |                                 |
|--------------------------------|---------------------|-----------------------------------|---------------------------------|
| • Elongation at break          | 200 %               | • Material                        | LDPE (Low-density polyethylene) |
| • Tensile strength             | 5.5 N/cm            | • Material of masking coverage    | LDPE                            |
| • Application temperature from | -5 °C               | • Residue-free removability       | yes                             |
| • Application temperature to   | 60 °C               | • Suitable for sensitive surfaces | yes                             |
| • Backing weight               | 29 g/m <sup>2</sup> | • Tear resistance                 | no                              |
| • Easy to remove               | yes                 | • Water resistance                | medium                          |

### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 0.8 N/cm |
|---------|----------|



# tesa<sup>®</sup> 74921

## Self-adhesive Protection Film

### Product Information

#### Storage Conditions

##### **Storage Conditions**

Storage should be in an environment away from sunlight, humidity between 40 and 70%, temperature between 15 and 30°C.

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?mp=74921>