



tesa[®] extra Power ECO REPAIR

Product Information

BNR 56431, 56432, 56435, 56436

Product Description

If you want a high-performance duct tape offering extra tear resistance and long-term durability tesa[®] extra Power Eco is the environment-friendly alternative.

Product Features

- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- Tear-resistant but easy to tear by hand
- Can be written on
- Available in black, grey and white

Environmental aspects:

- Natural and sustainable fibres
- 64% bio-based material
- Solvent-free natural rubber adhesive

Packaging:

- 80% recycled cardboard

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------|-------------------|--------|
| • Backing material | Acrylic-coated cloth | • Total thickness | 280 µm |
| • Type of adhesive | natural rubber | | |



tesa[®] extra Power ECO REPAIR

Product Information

Properties/Performance Values

• Tensile strength	70 N/cm	• Residue free removal	yes
• Adhesive strength	High adhesion	• Solvent free	yes
• Ageing resistance (UV)	yes	• Suitable surfaces	Even wood, Tiles, Brick, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone
• Application temperature from	+10 °C		
• Application temperature to	+50 °C		
• Area of use	Outdoor		
• Hand tearability	yes	• Tear resistance	yes
• Humidity resistance	yes	• Temperature resistance	yes
• Oil and grease resistance	no	• Tensibility	9 %
• Ozone resistance	yes	• UV-resistant	yes
		• Water resistance	yes
		• Waterproof	no
		• Writable	yes

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.