



tesa[®] Professional 64620 W

Product Information

Double-sided carpet laying tape

Product Description

tesa[®] Professional 64620 is a double-sided self-adhesive tape, consisting of a white PP-carrier and a synthetic rubber adhesive mass system (hotmelt). With the hotmelt adhesive, tesa[®] 64620 is solvent free and offers a high tack.

tesa[®] Professional 64620 is protected by a siliconized paper liner.

Product Features

- Floor laying
- General purpose mounting and fixation tape

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Backing material | PP film | • Total thickness | 185 µm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|------|-----------------------|------|
| • Elongation at break | 80 % | • Humidity resistance | good |
| • Hand tearability | good | | |

Adhesion to Values

- | | |
|---------|---------|
| • steel | 11 N/cm |
|---------|---------|



tesa® Professional 64620 W

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?mp=64620>