



# tesa® Professional 4411 Easy Cover® UV Precision

## Product Information

2-in-1 covering film

### Product Description

Easy Cover® 4411 UV Precision is a combination of a PE film and the tesa® Precision Mask Outdoor tape 4440, designed for masking of large areas in one working step. This product is especially suitable for outdoor applications whenever a clear and sharp paint edge is needed, especially on surfaces such as glass, aluminium and wood. Once applied, the maximum duration of 26 weeks of outdoor application leaves a comfortable time period for performing various working steps. The embossed film avoids paint bleeding or leaking to the protected area.

### Product Features

- Time-saving 2-in-1 covering solution for professionals: covering large areas and precise masking in one step
- Combination of LDPE masking film and integrated tesa® precision crepe 4440 Outdoor UV PLUS
- Ideally suited for clean and precise paint edges outdoors
- Application among others on glass, aluminum and wood
- 26 weeks UV resistance

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |             |                   |        |
|--------------------|-------------|-------------------|--------|
| • Backing material | Washi paper | • Total thickness | 110 µm |
| • Type of adhesive | acrylic     |                   |        |

### Properties/Performance Values

- |                       |         |                                |      |
|-----------------------|---------|--------------------------------|------|
| • Elongation at break | 5 %     | • Material of masking coverage | HDPE |
| • Tensile strength    | 35 N/cm | • Suitable for rough surfaces  | good |

### Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 1.8 N/cm |
|---------|----------|



# tesa® Professional 4411 Easy Cover® UV Precision

Product Information

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?mp=04411>