

tesa® Ultra Power Under Water Transparent repair tape

Product Information

56481, 56491

Product Description

The tesa® Ultra Power Under Water Transparent adhesive tape offers a reliable hold and protection in various conditions, such as moisture and heat. This makes it ideal for outdoor repairs, on wet surfaces or underwater.

Product Features

- Waterproof grip strength: This adhesive tape provides a reliable grip on wet surfaces and underwater
- Robust and durable: The extra-thick repair tape provides exceptionally strong adhesive strength
- Climate-proof resilience: UV and temperature resistance ensure effective repairs, at all times
- Resistance and flexibility: The abrasion-resistant repair tape adapts to various shapes and objects
- Versatile: Ideal for sealing holes, cracks or leaks, both indoors and outdoors
- Discreet: The transparent adhesive tape blends seamlessly with any surface

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------|-------------------|--------|
| • Backing material | PVC film | • Total thickness | 730 µm |
| • Type of adhesive | rubber based | | |

Properties/Performance Values

• Tensile strength	90 N/cm	• Residue free removal	no
• Abrasion resistance	yes	• Solvent free	no
• Adhesive strength	Very high adhesion	• Suitable surfaces	Most plastics, Glass, Metal, Steel
• Ageing resistance (UV)	yes	• Tear resistance	yes
• Area of use	In- and Outdoor	• Temperature resistance	yes
• Hand tearability	no	• UV-resistant	very good
• Oil and grease resistance	yes	• Waterproof	yes
• Ozone resistance	yes	• Writable	no

tesa® Ultra Power Under Water Transparent repair tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=56481DIY>